

Megadrain S

Drainage mats

Technical data

TenCate Polyfelt® Megadrain S is a drainage product made of three-dimensional polypropylene monofilaments combined with one or two layers of polypropylene filter geotextile. TenCate Polyfelt® Megadrain S has an extremely high voids content offering a high in-plane flow capacity. TenCate Polyfelt® Megadrain S drainage mats are used for surface drainage applications, replacing conventional drainage gravel layers.



TenCate Polyfelt® Megadrain S

Properties [Standard]	Unit	29-107	59-120	14-206	27-207	38-215	59-220
Type of product	-	Drainage composite with filter on one side		Drainage composite with filter on both sides			
Raw material	-	PP (monofilament mat) + PP UV-stabilized (filter)					
In-plane flow capacity*							
		s/h	s/h	s/h	s/h	s/h	s/h
i = 1	20 kPa l/(m/s)	2.90	5.93	1.40	2.70	3.80	5.93
	50 kPa l/(m/s)	2.50	2.70	1.20	2.30	2.20	2.60
	100 kPa l/(m/s)	2.00	1.00	0.90	1.80	0.80	1.00
i = 0.01	20 kPa l/(m/s)	0.74	1.62	0.32	0.70	1.20	1.62
[EN ISO 12958]	50 kPa l/(m/s)	0.68	1.20	0.28	0.57	0.70	1.00
	100 kPa l/(m/s)	0.62	0.35	0.25	0.45	0.30	0.30
Thickness [EN ISO 9863-1]	2 kPa mm	7	20	5.5	7	15	20
Tensile strength [EN ISO 10319]	kN/m	6/8	6/8	12/16	12/16	12/16	12/16

Filter geotextile	all grades	Properties	Unit	all grades
Type of product	Mechanically bonded continuous-filament nonwoven	Cone drop test [EN ISO 13433]	mm	30
		Tensile strength MD / CD [EN ISO 10319]	kN/m	6 / 8
		CBR puncture resistance [EN ISO 12236]	N	1100
		Opening size O90 [EN ISO 12956]	µm	130
		Water permeability [EN ISO 11058, Δh = 50 mm]	l/m ² .s (mm/s)	140

Forms of supply	Unit	29-107	59-120	14-206	27-207	38-215	59-220
Length [±2%]	m	77	25	83	68	33	25
Width [±3%]	m	2,4	2,4	2,4	2,4	2,4	2,4
Roll diameter	mm	800	800	800	800	800	800

*1) Tolerance -20%

The values given are average values obtained in our laboratories and in testing institutes. The right is reserved to make changes without notice at any time.

TENCATE GEOSYNTHETICS AUSTRIA GMBH

Schachermayerstr. 18 Tel. +43 732 6983 0, Fax +43 732 6983 5353
A-4021 Linz, Austria service.at@tencategeo.com, www.tencategeo.at

BeNeLux
Central Eastern Europe
Czech Republic
France | Africa
Germany
Italy
Near Middle East

Tel. +31 546 544 811 service.nl@tencategeo.com
Tel. +43 732 6983 0 service.at@tencategeo.com
Tel. +420 2 2425 1843 service.cz@tencategeo.com
Tel. +33 1 34 23 53 63 service.fr@tencategeo.com
Tel. +49 30 3435 02 10 service.de@tencategeo.com
Tel. +39 0362 34 58 11 service.it@tencategeo.com
Tel. +971 4810 3295 service.nme@tencategeo.com

Poland
Russia | CIS
Scandinavia | Baltics
Spain | Portugal
Switzerland
Turkey
UK | Ireland

Tel. +33 1 34 23 53 63 service.pl@tencategeo.com
Tel. +43 732 6983 0 service.ru@tencategeo.com
Tel. +31 546 544 811 geonordie@tencategeo.com
Tel. +34 607 499 962 service.es@tencategeo.com
Tel. +49 30 3435 02 10 service.ch@tencategeo.com
Tel. +43 732 5893 0 service.tr@tencategeo.com
Tel. +44 1952 588 066 service.uk@tencategeo.com



TenCate Geosynthetics Austria Gesm.b.H, TenCate Geosynthetics France S.A.S and TenCate Geosynthetics Netherlands b.v. are certified for the design, manufacturing and sales of geotextile and geotextile related products.



503463 | 03.2019 | EN | SC.SH